



ALLOWABLE SPANS		
	SPACING	SPAN
2x6	16	14'-0"
	24"	11'-0"
	32	10'-0"
	48	8'-0"
HEADERS	4x4	5'-0"
	4x6	8'-0"
	4x8	11'-0"
	4x10	14'-0"

← LIMIT TO 8' AS SHOWN
← USE FOR PLAN SHOWN

GENERAL NOTES

- 1 DIMENSIONS HAVE PREFERENCE OVER SCALE
- 2 CONTRACTOR SHALL VERIFY ALL DIMENSIONS & CONDITIONS @ EACH JOB SITE
- 3 ALL PHASE OF CONSTRUCTION SHALL COMPLY W/THE CURRENT ED OF THE USC AND/OR STATE & LOCAL CODES
- 4 CONTRACTOR SHALL SECURE & PAY FOR ALL PERMITS REQD BY PCM & THE OC BUILDING DEPT
- 5 UPON COMPLETION CONTRACTOR SHALL REMOVE ALL DEBRIS AND LEAVE AREA OF WORK BROOM CLEAN
- 6 ALL WOOD MEMBERS SHALL BE STAINED TO MATCH EXISTING TRIM METAL TO BE PAINTED FLAT BLACK
- 7 VERTICAL FRAMING SHALL BE STUD GRADE OR BETTER HORIZONTAL FRAMING TO BE #2 DF L OR BETTER
- 8 CONCRETE TO BE 2000 PSI @ 28 DAYS CONCRETE THAT WILL BE EXPOSED TO SOIL CONTAINING SULFATE CONCENTRATIONS OF MORE THAN 02% SHALL BE MADE W/TYPE I CEMENT
- 9 ALL FASTENERS EXPOSED TO WEATHERING SHALL BE GALVANIZED
- 10 PATIO COVER DESIGNED FOR LL=10 PSF DL=5 PSF
- 11 FOR CALCULATIONS SEE STD PLAN 70-387, DATED 3-1-73



(73-462)

LA PRINCESA (PLAN 41 & 41R)
OPEN LATTICE PATIO COVER REAR

LEISURE WORLD
STANDARD PLAN
NUMBER _____

PROFESSIONAL COMMUNITY MGMT INC
APPROVED _____

APPROVED BY *R. Cam*
PCM INC 383-7616
P.O. BOX 2220 LAGUNA HILLS

July 10 1974